

— explanatory note —

The seat drop value described in the compatibility table is primarily a value relative to the original-equipment seat. It is measured by mounting a Recaro or Bride full bucket seat at the lowest position possible without the seat bottom interfering with the seat rail or vehicle floor. Differences may arise due to the position of the seat to be mounted (the position of the bolt holes), the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: If the original-equipment seat incorporates a height adjustment function, this value is relative to the lowest position.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

FRANCE

CITROEN

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
AX	ZAKD,ZAKF	-15mm	S1	ICN1140S01R	ICN1140S01L	NPC003	Seat drop is from Model 106(S10) specifications.
AX	ZAKD,ZAKF	-40mm	S1	ICN1150S01R	ICN1150S01L	NPC003	Superlow model. Seat drop is from Model 106(S10) specifications.
BERLINGO	K9CYH01	±0mm	S36	ICN1190S36R	ICN1190S36L	NPC002	Right-hand drive car.
BERLINGO	K9CYH01	±0mm	S36	ICN1191S36R	ICN1191S36L	NPC002	Left-hand drive car.
C2	A6KFV,A6NFU	-15mm	S6	ICN1030S06R	ICN1030S06L	NPC003	Seat drop is from Model 307(T5) specifications.
C2	A6KFV,A6NFU	-15mm	LS9	ICN1030S09R	ICN1030S09L	NPC003	Seat drop is from Model 307(T5) specifications.
C2	A6KFV,A6NFU	-40mm	S1	ICN1160S01R	ICN1160S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Seat drop is from Model 307(T5) specifications.
C3	A8KFV,A8NFU	-15mm	S6	ICN1031S06R	ICN1031S06L	NPC003	Seat drop is from Model 307(T5) specifications.
C3	A8KFV,A8NFU	-15mm	LS9	ICN1031S09R	ICN1031S09L	NPC003	Seat drop is from Model 307(T5) specifications.
C3	A8KFV,A8NFU	-40mm	S1	ICN1161S01R	ICN1161S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Seat drop is from Model 307(T5) specifications.
C3	B6HN05,B6HN01	-10mm	S36	ICN1180S36R	ICN1180S36L	NPC001	
C3	B6HN05,B6HN01	±0mm	LS9	ICN1180S09R	ICN1180S09L	NPC001	
C4	B5RFK,B5RFJ,B5NFU	-20mm	S6	ICN1070S06R	ICN1070S06L	NPC002	Offset toward door side is 10 mm. All seats are linked to seat belt warning lamps (without surface pressure sensors).
C4	B55FT,B55FW	-20mm	S6	ICN1071S06R	ICN1071S06L	NPC002	Offset toward door side is 10 mm. All seats are linked to seat belt warning lamps (without surface pressure sensors). Seat drop is from Model 307(T5) specifications.
C4	B55FT,B55FW	-40mm	S1	ICN1162S01R	ICN1162S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Seat drop is from Model 307(T5) specifications.

C4	B75F01,B75F02	-20mm	S6	ICN1080S06R	ICN1080S06L	NPC002	Offset toward door side is 5 mm. Relocation of passenger seat pressure sensor is required. Seat drop is from Model 308(T9) specifications.
C4	B7BH01	-20mm	S6	ICN1200S06R	ICN1200S06L	NPC001	Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required. B7HN02 is unconfirmed.
C4 Picasso	B58RFJP	-10mm	S36	ICN1060S36R	ICN1060S36L	NPC002	Relocation of the pretensioner is required.
C4 Picasso	B785G01,B78AH01	±0mm	S36	ICN1170S36R	ICN1170S36L	NPC003	Relocation of passenger seat pressure sensor is required. Carefully note the color of the wiring for the side airbags.
C5	X7RFJ,X7XFV	-10mm	S4	ICN1090S04R	ICN1090S04L	NPC002	Offset toward door side is 8 mm. Relocation of passenger seat pressure sensor is required. Seat drop is from Model 407(D2) specifications.
DS3	A5C	±0mm	S6	ICN1100S06R	ICN1100S06L	NPC002	
DS5	B85F02	±0mm	S36	ICN1210S36R	ICN1210S36L	NPC002	Unit, surface pressure sensor relocation required.
SAXO	S8NFS	-15mm	S1	ICN1141S01R	ICN1141S01L	NPC003	Seat drop is from Model 106(S10) specifications.
SAXO	S8NFS	-40mm	S1	ICN1151S01R	ICN1151S01L	NPC003	Superlow model. Seat drop is from Model 106(S10) specifications.
XANTIA	X1RF,X2RF	-15mm	S1	ICN1130S01R	ICN1130S01L	NPC003	'93/10~'98/09 Cannot be installed on vehicles equipped with The pretensioner
ZX	N2	-15mm	S1	ICN1120S01R	ICN1120S01L	-	5door

PEUGEOT

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
106	S10,S2S	-15mm	S1	IPT1010S01R	IPT1010S01L	NPC003	
106	S10,S2S	-45mm	S1	IPT1070S01R	IPT1070S01L	NPC003	Superlow model.
205	20D	±0mm	S1	IPT1020S01R	IPT1020S01L	-	
206	T16,T14,M206CC	-15mm	S4	IPT1030S04R	IPT1030S04L	NPC003	Seat drop is from Model hatchback specifications.
206	T16,T14,M206CC	-50mm	S1	IPT1080S01R	IPT1080S01L	NPC003	Superlow model.
207	A7#	-15mm	S6	IPT1092S06R	IPT1092S06L	NPC003	Seat drop is from Model 307(T5) specifications.
207	A7#	-15mm	LS9	IPT1092S09R	IPT1092S09L	NPC003	Seat drop is from Model 307(T5) specifications.
207	A7#	-40mm	S1	IPT1212S01R	IPT1212S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Seat drop is from Model 307(T5) specifications.
208	A9HM01,A9HN01	-15mm	S6	IPT1093S06R	IPT1093S06L	NPC003	Relocation of passenger seat pressure sensor is required. Seat drop is from Model 307(T5) specifications.
208	A9HM01,A9HN01	-15mm	LS9	IPT1093S09R	IPT1093S09L	NPC003	Relocation of passenger seat pressure sensor is required. Seat drop is from Model 307(T5) specifications.

208	A9HM01,A9HN01	-40mm	S1	IPT1213S01R	IPT1213S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Relocation of passenger seat pressure sensor is required. Seat drop is from Model 307(T5) specifications.
208	P21HN05	±0mm	S6	IPT1260S06R	IPT1260S06L	NPC001	Relocation of passenger seat pressure sensor is required.
208	P21HN05	-30mm	S1	IPT1270S01R	IPT1270S01L	NPC001	Superlow model. Relocation of passenger seat pressure sensor is required.
2008	A94HM01	-15mm	S6	IPT1094S06R	IPT1094S06L	NPC003	Relocation of passenger seat pressure sensor is required. Seat drop is from Model 307(T5) specifications.
2008	A94HM01	-15mm	LS9	IPT1094S09R	IPT1094S09L	NPC003	Relocation of passenger seat pressure sensor is required. Seat drop is from Model 307(T5) specifications.
2008	A94HM01	-40mm	S1	IPT1214S01R	IPT1214S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Relocation of passenger seat pressure sensor is required. Seat drop is from Model 307(T5) specifications.
2008	P24HN05	-10mm	S36	IPT1280S36R	IPT1280S36L	NPC002	Seat drop is from Model C3(B6H)specifications.
2008	P24HN05	±0mm	LS9	IPT1290S09R	IPT1290S09L	NPC002	Seat drop is from Model C3(B6H)specifications.
3008	T85F02	±0mm	S36	IPT1110S36R	IPT1110S36L	NPC002	Relocation of passenger seat pressure sensor is required.
3008	P845G01,P84AH01	-20mm	S36	IPT1230S36R	IPT1230S36L	NPC002	Relocation of the pretensioner,slide sensor,passenger seat pressure sensor is required.
306	N3,N5	-15mm	S1	IPT1120S01R	IPT1120S01L	-	3door,4door
306	N3,N5	-15mm	S1	IPT1130S01R	IPT1130S01L	-	5door
306	N3C,N5C	-10mm	S1	IPT1140S01R	IPT1140S01L	-	Designed exclusively for Model Cabriolet specification.
307	T5#	-15mm	S6	IPT1090S06R	IPT1090S06L	NPC003	Relocation of passenger seat pressure sensor is required.
307	T5#	-15mm	LS9	IPT1090S09R	IPT1090S09L	NPC003	Relocation of passenger seat pressure sensor is required.
307	T5#	-40mm	S1	IPT1210S01R	IPT1210S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Relocation of passenger seat pressure sensor is required.
307	T7#	-15mm	S6	IPT1091S06R	IPT1091S06L	NPC003	Relocation of passenger seat pressure sensor is required.
307	T7#	-15mm	LS9	IPT1091S09R	IPT1091S09L	NPC003	Relocation of passenger seat pressure sensor is required.
307	T7#	-40mm	S1	IPT1211S01R	IPT1211S01L	NPC003	Superlow model. 45-mm rearward offset compared with standard model. Relocation of passenger seat pressure sensor is required.
308,308SW	T9	-20mm	S6	IPT1160S06R	IPT1160S06L	NPC002	Relocation of passenger seat pressure sensor is required.
405	15DFV,D70	-20mm	S1	IPT1040S01R	IPT1040S01L	-	
406	D8,D9	-20mm	S1	IPT1050S01R	IPT1050S01L	NPC003	
406	D8,D9	-20mm	S1	IPT1170S01R	IPT1170S01L	NPC003	Designed exclusively for Model coupe specification.
407	D2	-10mm	S4	IPT1060S04R	IPT1060S04L	NPC001	Offset toward door side is 8 mm. Relocation of passenger seat pressure sensor is required.
5008	P87,T87	不明	S36	IPT1240S36R	IPT1240S36L	NPC002	Relocation of passenger seat pressure sensor is required.

PARTNER	-	-30mm	S4	IPT1200S04R	IPT1200S04L	-	
RCZ	T7R5	-20mm	S1	IPT1180S01R	IPT1180S01L	NPC003	Offset toward door side is 20 mm. Relocation of passenger seat pressure sensor is required. The orientation of the seat belt anchor differs depending on whether it is bottom-mounted or side-mounted.
RIFTER	K9PYH01	±0mm	S36	IPT1300S36R	IPT1300S36L	NPC002	Right-hand drive car.
RIFTER	K9PYH01	±0mm	S36	IPT1301S36R	IPT1301S36L	NPC002	Left-hand drive car.

RENAULT

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
5 CINQ TURBO	-	-20mm	S1	IRT1010S01R	IRT1010S01L	-	Fixed pitch confirmation required, front/rear 285mm x left/right 475mm
5 CINQ,CINQ TURBO	C405,C407,C408	-40mm	S4	IRT1020S04R	IRT1020S04L	-	
ALPINE A110	DFM5P	-10mm	S1	IRT1200S01R	IRT1200S01L	-	Offset toward door side is 20 mm. Seats with a convex bottom (such as AM19) are not compatible. Interferes with shoulder width exceeding 560 mm. Seat drop is from Model pure(Original-equipment full bucket seat) specifications.
CAPTUR	2RH5F	-20mm	S16	IRT1194S16R	IRT1194S16L	NPC001	Require a canceller (NPC001×2). Seat drop is from Model LUTECIA(RK4M) specifications.
EXPRESS	F402	-40mm	S4	IRT1021S04R	IRT1021S04L	-	
KANGOO	KCK4M,KCK7J	-30mm	S4	IRT1040S04R	IRT1040S04L	NPC003	
KANGOO	KWK4M,KWH5F	-20mm	S36	IRT1030S36R	IRT1030S36L	NPC001	Offset toward door side is 10 mm.
KOLEOS	Y2TR	-20mm	S36	IRT1060S36R	IRT1060S36L	NPC001	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
LUTECIA	BK,BF,BL7X	-15mm	S1	IRT1170S01R	IRT1170S01L	NPC003	
LUTECIA	BK,BF,BL7X	-35mm	SSD	IRT1180SSDR	IRT1180SSDL	NPC003	
LUTECIA	RK4M,RF4C	-20mm	S16	IRT1190S16R	IRT1190S16L	NPC001	Offset toward door side is 20 mm. Require a canceller (NPC001×2).
LUTECIA	RH5F,RM5M,RH4B	-20mm	S16	IRT1191S16R	IRT1191S16L	NPC001	Offset toward door side is 20 mm. Require a canceller (NPC001×2). Seat drop is from Model LUTECIA(RK4M) specifications.
MEGANE	AF3R2,AF3R2,AK4M	-20mm	S1	IRT1140S01R	IRT1140S01L	NPC003	Coupe,Cabriolet
MEGANE	AF3RJ	-15mm	S1	IRT1162S01R	IRT1162S01L	-	Designed exclusively for Model Scenic(1BOX) specification.
MEGANE	MF4,MK4,KMF4	-15mm	S16	IRT1150S16R	IRT1150S16L	NPC003	Offset toward door side is 5 mm. Require a canceller (NPC003×2). Relocation of passenger seat pressure sensor is required. Interferes with shoulder width exceeding 580 mm. Compatibility with Cabriolet vehicles to be confirmed.
MEGANE	DZF4R,ZM4R	-10mm	S6	IRT1120S06R	IRT1120S06L	NPC001	Offset toward door side is 10 mm.
MEGANE	BBM5P,BBM5M BBH5F,KBM5M	-10mm	S6	IRT1220S06R	IRT1220S06L	NPC002	Offset toward door side is 10 mm. Relocation of The pretensioner and Various sensors is required.

MEGANE ESTATE	KZF4R	-10mm	S6	IRT1130S06R	IRT1130S06L	NPC001	Relocation of the pretensioner is required.
SCENIC	AF3RJ	-15mm	S1	IRT1160S01R	IRT1160S01L	-	
SCENIC	AF4RJ	-15mm	S1	IRT1161S01R	IRT1161S01L	NPC003	
TWINGO	06C3G,06D7F	-25mm	S1	IRT1090S01R	IRT1090S01L	NPC003	
TWINGO	ND4M,NK4M	-10mm	S6	IRT1100S06R	IRT1100S06L	NPC001	Relocation of slide sensor is required. Interferes with shoulder width exceeding 560 mm.
TWINGO	ND4M,NK4M	-10mm	LS9	IRT1100S09R	IRT1100S09L	NPC001	Relocation of slide sensor is required. Interferes with shoulder width exceeding 560 mm.
TWINGO	AHH4B,AHB4D	+10mm	S6	IRT1210S06R	IRT1210S06L	NPC001	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
TWINGO	AHH4B,AHB4D	-20mm	S1	IRT1230S01R	IRT1230S01L	NPC001	Superlow model. Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
WIND	ENK4M	-10mm	S6	IRT1101S06R	IRT1101S06L	NPC001	Interferes with shoulder width exceeding 560 mm. Seat drop is from Model TWINGO(ND4M,NK4M) specifications.
WIND	ENK4M	-10mm	LS9	IRT1101S09R	IRT1101S09L	NPC001	Interferes with shoulder width exceeding 560 mm. Seat drop is from Model TWINGO(ND4M,NK4M) specifications.