

— explanatory note —

Differences may arise due to the position of the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
DUTRO	BU100系	+15mm	B1	DHI1060B01R	-	-	Seat drop is from Model xx specifications.DYNA2.8 L track Offset toward door side is 10 mm. Only for driver's seat. The seat belt anchor is fixed to the floor. Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
DUTRO	U400系	+15~20mm	B1	DHI1160B01R	-	-	Confirmation of fixed pitch is required. For wide cab vehicles.
DUTRO	U400系	±0~-5mm	B6	-	DHI1170B06L	-	Confirmation of fixed pitch is required. For wide cab vehicles. The seat belt anchor is fixed to the floor. The 2 points behind the rail are diverted from the genuine belt fixing part. Floor drilling required on the front right side of the rail.
DUTRO	C700系,U700系	-30mm	B1	DHI1090B01R	-	-	Installation dimensions must be confirmed. For wide cab vehicles only. Offset toward door side is 10 mm. AM19 requires a 20mm spacer with or without electric function. Only for driver's seat.
LIESSE	RX4	No data	B6	DHI1110B06R	DHI1110B06L	-	Confirmation of fixed pitch is required. Microbus. The seat belt anchor is fixed to the floor.
LIESSE	No data	-30mm	B16	DHI1130B16R	-	-	Confirmation of fixed pitch is required. Microbus. Unconfirmed car with passenger door. Bottom convex sheet not possible (AM19, etc.). Seat rail conversion adapter cannot be installed
LIESSE	No data	-30mm	B16	-	DHI1140B16L	-	Confirmation of fixed pitch is required. Microbus. Unconfirmed car with passenger door.

PROFIA 10t	No data	No data	B6	DHI1100B06R	-	-	Confirmation of fixed pitch is required. Use genuine base. Only for driver's seat. The seat belt anchor is fixed to the floor.
SPACE DOLPHIN 10t	No data	No data	B6	DHI1010B06R	-	-	Confirmation of fixed pitch is required. Use genuine base. The seat belt anchor is fixed to the floor.
RANGER	GX7JGFA改,FD1JJBA	No data	B6	DHI1120B06R	DHI1120B06L	-	Confirmation of fixed pitch is required. The seat belt anchor is fixed to the floor.
RANGER	FE7J###,FC7J### FC6J###	±0mm	B6	DHI1150B06R	-	-	Confirmation of fixed pitch is required. Use genuine base. The seat belt anchor is fixed to the floor.