

— explanatory note —

The seat drop value described in the compatibility table is primarily a value relative to the original-equipment seat. It is measured by mounting a Recaro or Bride full bucket seat at the lowest position possible without the seat bottom interfering with the seat rail or vehicle floor. Differences may arise due to the position of the seat to be mounted (the position of the bolt holes), the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: If the original-equipment seat incorporates a height adjustment function, this value is relative to the lowest position.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

ISUZU

| Model Name | Model Code | Seat Drop | Type | Right Part No. | Left Part No. | Side SRS | Remarks |
|--------------------------|----------------------------|-----------|------|----------------|---------------|----------|--|
| BIGHORN | UBS25,UBS69 | -20mm | S4 | DIU1070S04R | DIU1070S04L | - | 2 doors (short body) can be installed only in the passenger seat. |
| ELF | R60 | +10mm | S1 | DIU1020S01R | - | - | Mounting dimensions required. The seat belt anchor is fixed to the floor. Seat rail conversion adapter cannot be installed. 1-position offset seat rail. |
| ELF | R66,R69,R71 R72,R75,R81 | +10mm | S1 | DIU1010S01R | - | - | Mounting dimensions required. The seat belt anchor is fixed to the floor. Seat rail conversion adapter cannot be installed. Common to ATLAS(H42). 1-position offset seat rail. |
| ELF | R85,S85 | ±0mm | S1 | DIU1100S01R | - | - | Mounting dimensions required. Interferes with seat width exceeding 495 mm. Offset toward door side is 15 mm. Wide cab is unconfirmed. |
| ELF Camping Car | ###85 | +15mm | S1 | DIU1110S01R | - | - | Mounting dimensions required. For vehicles that have been changed from a 3-seat front seat to a 2-seat seat. 1-position offset seat rail. |
| ELF SPACE CAB ELF mio | NJR88AF,NHR87AF | +20mm | S1 | DIU1120S01R | - | - | Offset toward door side is 15 mm. 1-position offset seat rail. |
| ELF 100 | ASQ2F24 | No data | S1 | DIU1030S04R | - | - | Mounting dimensions required. Common to ATLAS,TITAN,CANTER. |
| GIGA | CXZ | -70mm | S16 | DIU1040S16R | - | - | Mounting dimensions required. Offset toward door side is 10 mm. The genuine air suspension is used. |
| MU,WIZARD | UCS69 | -10mm | S1 | DIU1090S01R | DIU1090S01L | - | The seat belt anchor is fixed to the floor. |
| MU,WIZARD | UES25,UES73 | -10mm | S1 | DIU1080S01R | DIU1080S01L | - | |
| PIAZZA | JR120,JR130 | No data | S1 | DIU1050S01R | DIU1050S01L | - | The seat belt anchor is fixed to the floor. Need to check mounting dimensions. Front left and right 354 mm, rear left and right 367 mm. |