

The seat drop value described in the compatibility table is primarily a value relative to the original-equipment seat.

It is measured by mounting a Recaro Reclining seat.

— **explanatory note** — Differences may arise due to the position of the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: If the original-equipment seat incorporates a height adjustment function, this value is relative to the lowest position.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

## ITALY

### ABARTH

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
124 SPIDER	NF2EK	-10mm	B1	IAH1040B01R	IAH1040B01L	NPC001	Offset toward door side is 10 mm. Cannot be installed if dial width exceeds 500 mm. When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed. Common to ROADSTER(ND5RC). Numerical value is from Model ROADSTER(ND5RC) specifications.
500,595,695	312141,312142 31214B,31214T	±0mm	B36	IAH1010B36R	IAH1010B36L	NPC002	Relocation of passenger seat pressure sensor is required. Common to FIAT500(312#). Numerical value is from Model FIAT500(312#) specifications.
500,595,695	312141,312142 31214B,31214T	-35mm	B36	IAH1020B36R	IAH1020B36L	NPC002	Superlow model. If a woofer box is mounted on floor, it must be relocated. Relocation of passenger seat pressure sensor is required. Common to FIAT500(312#). Numerical value is from Model FIAT500(312#) specifications.
500,595,695	312141,312142 31214B,31214T	-30mm	LB25	IAH1020B25R	IAH1020B25L	NPC002	Superlow model. If a woofer box is mounted on floor, it must be relocated. Relocation of passenger seat pressure sensor is required. Common to FIAT500(312#). Numerical value is from Model FIAT500(312#) specifications.

### ALFA ROMEO

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
145	930A5	-15mm	B1	IAO1040B01R	IAO1040B01L	NPC003	
145	930A5	-30mm	B1	IAO1050B01R	IAO1050B01L	NPC003	Superlow model. Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
146	-	-15mm	B1	IAO1041B01R	IAO1041B01L	NPC003	Common to 145(930A5).

146	-	-30mm	B1	IAO1051B01R	IAO1051B01L	NPC003	Superlow model. Common to (930A5). Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
147	937AB	-20mm	B1	IAO1060B01R	IAO1060B01L	NPC003	Relocation of passenger seat pressure sensor is required.
147	937AB	-40mm	B1	IAO1070B01R	IAO1070B01L	NPC003	Superlow model. Offset toward door side is 10 mm. Reclining seats cannot be installed. Only for full bucket seat of bottom fixing type. Relocation of passenger seat pressure sensor is required.
156	932A	-20mm	B1	IAO1010B01R	IAO1010B01L	NPC003	Relocation of passenger seat pressure sensor is required.
156	932A	-45mm	B1	IAO1020B01R	IAO1020B01L	NPC003	Superlow model. Relocation of passenger seat pressure sensor is required. Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
159	93922,93932	-5mm	B16	IAO1080B16R	IAO1080B16L	NPC001	Offset toward door side is 33 mm. Relocation of passenger seat pressure sensor is required.
166	936A	-15mm	B1	IAO1030B01R	IAO1030B01L	NPC003	Relocation of passenger seat pressure sensor is required.
4C	96018	+20mm	B1	IAO1090B01R	IAO1090B01L	-	Offset toward door side is 8 mm. Interferes with shoulder width exceeding 600 mm. There is interference when the dial width is 500 mm or more. When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed.
75	162B40	No data	B1	IAO1100B01R	IAO1100B01L	-	
BRERA	93922S,93932S	-10mm	B6	IAO1110B06R	IAO1110B06L	NPC002	Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required.
GIULIA	95220,95229	±0mm	B6	IAO1170B06R	IAO1170B06L	NPC003	Offset toward door side is 5 mm. Relocation of passenger seat pressure sensor is required.,Relocation of the ECU is required. 4WD to be determined.
GIULIA	95220,95229	-15mm	B1	IAO1160B01R	IAO1160B01L	NPC003	Superlow model. Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required.,Relocation of the ECU is required. 4WD to be determined.
GIULIETTA	94014	-10mm	B6	IAO1120B06R	IAO1120B06L	NPC002	Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required.
GT	93720L	-20mm	B1	IAO1061B01R	IAO1061B01L	NPC003	Relocation of passenger seat pressure sensor is required.

GT	93720L	-40mm	B1	IAO1071B01R	IAO1071B01L	NPC003	Superlow model. Offset toward console side is 10 mm. Relocation of passenger seat pressure sensor is required.
GTV	916	±0mm	B1	IAO1130B01R	IAO1130B01L	NPC003	Relocation of passenger seat pressure sensor is required. IS24&AM19 cannot be installed.
MITO	955	-20mm	B36	IAO1140B36R	IAO1140B36L	NPC002	Offset toward door side is 5 mm. Interferes with shoulder width exceeding 580 mm. Relocation of passenger seat pressure sensor is required.
SPIDER	916	±0mm	B1	IAO1131B01R	IAO1131B01L	NPC003	Relocation of passenger seat pressure sensor is required. IS24&AM19 cannot be installed.
SPIDER	93922S,93932S	-10mm	B6	IAO1111B06R	IAO1111B06L	NPC002	Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required.
RZ,SZ	-	-10mm	B1	IAO1150B01R	IAO1150B01L	-	When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed.
RZ,SZ	-	-10mm	B1	IAO1151B01R	IAO1151B01L	-	Dedicated for mounting IS24&AM19 series.

## AUTOBIANCHI

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
A112	-	-10mm	B6	IAU1010B06R	IAU1010B06L	-	'83~'85 Only digital clock cars can be installed. ~'82 It cannot be installed on analog clock cars. Hold the stay on the original-equipment slide rail and secure it.

## Ferrari

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
308 GT4	-	±0mm	B1	IFI1100B01R	IFI1100B01L	-	4 passengers AM19 requires a 20mm spacer with or without electric function.
348	F348	±0mm	B1	IFI1030B01R	IFI1030B01L	-	Need to check mounting dimensions. Front and rear 448 mm,Left and right 344 mm.
348	F348	±0mm	B1	IFI1130B01R	IFI1130B01L	-	Need to check mounting dimensions. Front and rear 346 mm,Left and right 344 mm.
355	F355	±0mm	B1	IFI1120B01R	IFI1120B01L	-	Front and back 295mm x left and right 405mm seat installation only. IS24&Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
360	F360	-10mm	B1	IFI1041B01R	IFI1041B01L	-	

430	F430	+10mm	B1	IFI1061B01R	IFI1061B01L	-	Offset toward door side is 15 mm. Seat drop is from Model Scuderia specifications. Seats with a convex bottom (such as AM19) interfere with the bottom of the height adjustment.
458 ITALIA	F142	-10mm	B1	IFI1090B01R	IFI1090B01L	NPC001	Offset toward door side is 20 mm. specialty garage recommended for installation. Common to spider.
550	F550	+10mm	B1	IFI1070B01R	-	-	Offset toward door side is 18 mm. When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed.
575	F575	+10mm	B1	IFI1071B01R	-	-	Offset toward door side is 18 mm. When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed.
F599	F599	-10mm	B1	IFI1060B01R	IFI1060B01L	-	Offset toward door side is 15 mm. Common to F430.
F8	F142CE	+25mm	B1	IFI1140B01R	IFI1140B01L	-	Offset toward door side is 9 mm. specialty garage recommended for installation. Common to Spider and Triboot.

## FIAT

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
131 ABARTH RALLY	-	±0mm	B1	IFT1120B01R	IFT1120B01L	-	
500	31209,31212,31214	±0mm	B36	IFT1070B36R	IFT1070B36L	NPC002	Relocation of passenger seat pressure sensor is required.
500	31209,31212,31214	-35mm	B36	IFT1080B36R	IFT1080B36L	NPC002	Superlow model. If a woofer box is mounted on floor, it must be relocated. Relocation of passenger seat pressure sensor is required.
500	31209,31212,31214	-30mm	LB25	IFT1080B25R	IFT1080B25L	NPC002	Superlow model. If a woofer box is mounted on floor, it must be relocated. Relocation of passenger seat pressure sensor is required.
BARCETTA	183A1	-10mm	B1	IFT1030B01R	IFT1030B01L	-	Relocation of passenger seat pressure sensor is required. Seats with a convex bottom (such as AM19) are not compatible.
COUPE FIAT	175A	-10mm	B4	IFT1010B04R	IFT1010B04L	-	
DUCATO	-	-25mm	B36	IFT1130B36R	IFT1130B36L	-	3rd generation '06-'15 before M/C Fixed to genuine turntable (fixed width 398mm) Common to Manager(Peugeot).

DUCATO	-	-45mm	B6	IFT1140B06R	IFT1140B06L	-	3rd generation '06-'15 before M/C Superlow model. Fixed to genuine turntable (fixed width 398mm) Common to Manager(Peugeot).
DUCATO	-	-25mm	B36	IFT1101B36R	IFT1101B36L	-	3rd generation '06-'15 before M/C Fixed to genuine turntable (fixed width 410mm) Common to Manager(Peugeot).
DUCATO	-	-45mm	B6	IFT1111B06R	IFT1111B06L	-	3rd generation '06-'15 before M/C Superlow model. Fixed to genuine turntable (fixed width 410mm) Common to Manager(Peugeot).
DUCATO	-	-25mm	B36	IFT1100B36R	IFT1100B36L	-	3rd generation '16- After M/C Fixed to genuine turntable (fixed width 410mm) Common to Manager(Peugeot).
DUCATO	-	-45mm	B6	IFT1110B06R	IFT1110B06L	-	3rd generation '16- After M/C Superlow model. Fixed to genuine turntable (fixed width 410mm) Common to Manager(Peugeot).
DOBLO	K9FYH01	±0mm	B36	IFT1150B36R	IFT1150B36L	NPC001	Right-hand drive car.
DOBLO	K9FYH01	-20mm	LB25	IFT1150B25R	IFT1150B25L	NPC001	Right-hand drive car.
DOBLO	K9FYH01	±0mm	B36	IFT1151B36R	IFT1151B36L	NPC001	Left-hand drive car.
DOBLO	K9FYH01	-20mm	LB25	IFT1151B25R	IFT1151B25L	NPC001	Left-hand drive car.
GRANDE PUNTO	199	-10mm	B36	IFT1020B36R	IFT1020B36L	NPC002	Interferes with shoulder width exceeding 580 mm. Relocation of passenger seat pressure sensor is required.
NEW PANDA	16912	-25mm	B16	IFT1040B16R	IFT1040B16L	NPC001	
PANDA	13909	±0mm	B36	IFT1071B36R	IFT1071B36L	NPC002	Relocation of passenger seat pressure sensor is required.
PANDA	13909	-35mm	B36	IFT1081B36R	IFT1081B36L	NPC002	Superlow model. If a woofer box is mounted on floor, it must be relocated. Relocation of passenger seat pressure sensor is required.
PANDA	13909	-30mm	LB25	IFT1081B25R	IFT1081B25L	NPC002	Superlow model. If a woofer box is mounted on floor, it must be relocated. Relocation of passenger seat pressure sensor is required.
PUNTO	176AR5,176BV3	-20mm	B4	IFT1060B04R	IFT1060B04L	NPC003	Pretensioner cannot be installed.
PUNTO	188A1,188A5	-10mm	B1	IFT1050B01R	IFT1050B01L	NPC003	Common to 147(937AB).

## LAMBORGHINI

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
------------	------------	-----------	------	----------------	---------------	----------	---------

AVENTADOR	47L539	No data	B1	ILI1010B01R	ILI1010B01L	-	Error code is generated when the seat is installed or removed (Diagnostic machine required). AM19 requires a 20mm spacer with or without electric function.
GALLARDO	-	±0mm	B1	ILI1030B01R	ILI1030B01L	NPC003	Interferes with dial width exceeds 500 mm. Interferes with shoulder width exceeding 580 mm. All plastic parts of the console must be removed. When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat.
HURACAN	ZFCSJ	No data	B1	ILI1050B01R	ILI1050B01L	NPC001	No installation data * Please contact us

## LANCIA

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
DELTA INTEGRALE	L31	-15mm	B1	ILA1010B01R	ILA1010B01L	-	Front and back 260 (235) mm × left and right 405 mm or Front and back 295mm x left and right 405mm seat installation only. Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
DELTA INTEGRALE	L31	-30mm	B1	ILA1020B01R	ILA1020B01L	-	Front and back 330mm x left and right 290mm seat installation only. Seat rail conversion adapter cannot be installed.
MUSA	-	-10mm	B36	ILA1040B36R	ILA1040B36L	-	Interferes with shoulder width exceeding 560 mm.

## MASERATI

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
GHIBLI	E-MG	-15mm	B6	IMA1010B06R	IMA1010B06L	-	Offset toward door side is 6 mm. '92~'97
GRAN TURISMO	MMC,MGT	-20mm	B1	IMA1020B01R	IMA1020B01L	-	When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed. Sparco SPX is ± 0 mm.
GRAN TURISMO	MMC,MGT	-20mm	B1	IMA1021B01R	IMA1021B01L	-	Dedicated for mounting IS24 & AM19 series