

The seat drop value described in the compatibility table is primarily a value relative to the original-equipment seat.

It is measured by mounting a Recaro Reclining seat.

— **explanatory note** — Differences may arise due to the position of the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: If the original-equipment seat incorporates a height adjustment function, this value is relative to the lowest position.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

MITSUBISHI

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
AIRTREK	CU2W,CU4W	-20mm	B4	DMI1120B04R	DMI1120B04L	NPC001	Offset toward door side is 5 mm.
CANTER	FE437F	No data	B1	DMI1580B01R	-	-	Mounting dimensions required. 5generation AM19 requires a 20mm spacer with or without electric function.
CANTER	FE50EB	No data	B1	DMI1610B01R	-	-	Mounting dimensions required. 6generation When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed.
CANTER	FE50EB	No data	B1	-	DMI1620B01L	-	Mounting dimensions required. 6generation Adapter only (no slide rail). Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
CANTER WIDECAB	FE638EV	+10mm	B1	DMI1550B01R	-	-	Mounting dimensions required. 6generation,wide Offset toward door side is 12 mm. AM19 requires a 20mm spacer with or without electric function.
CANTER	FE71D,FG73DC	No data	B1	DMI1560B01R	-	-	Mounting dimensions required. 7generation When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. AM19 cannot be installed.
CANTER WIDECAB	FEB50	-20mm	B6	DMI1660B06R	-	-	Mounting dimensions required. 9generation
CANTER GUTS	TZ2F24	No data	B4	DMI1570B04R	-	-	Mounting dimensions required.
CHALLENGER	K94W~K97W,K99W	-20mm	B4	DMI1230B04R	DMI1230B04L	-	'96/06~'99/05 The K99W passenger seat is compatible with 99/06 and later vehicles. Not compatible with full-time 4WD models with center differential.
CHALLENGER	K99W	-15mm	B4	DMI1231B04R	DMI1250B04L	-	'99/06~ Car with full-time 4WD with center differential.
CHARIOT	N30W,N40W	-20mm	B4	DMI1200B04R	DMI1200B04L	-	
CHARIOT GRANDIS	N84W,N86W,N94W,N96W	-20mm	B4	DMI1210B04R	DMI1210B04L	NPC001	

COLT	Z20A~Z28A Z23W,Z24W,Z27W	±0mm	B6	DMI1180B06R	DMI1180B06L	NPC001	Offset toward door side is 5 mm.
DELICA D:2	MB15S	-30mm	B36	DMI1300B36R	DMI1300B36L	NPC001	Offset toward console side is 25 mm. Interferes with shoulder width exceeding 615 mm.
DELICA D:2	MB36S,MB46S	-10mm	B36	DMI1310B36R	DMI1310B36L	NPC001	
DELICA D:2	MB37S	-20mm	B36	DMI1720B36R	DMI1720B36L	NPC001	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
DELICA D:2	MB37S	-20mm	LB25	DMI1720B25R	DMI1720B25L	NPC001	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
DELICA D:3	BM20	-10mm	B1	DMI1690B01R	DMI1690B01L	-	Used as a pedestal Common to NV200(M20). The amount of down is NV200 (M20) data.
DELICA D:5	CV5W,CV1W	-30mm	B36	DMI1290B36R	DMI1290B36L	-	No side airbag, as curtain airbag is installed. For vehicles after minor change ('19 .11 ~), the error warning light of the airbag will light up unless the blue coupler itself under the genuine seat is relocated.
DELICA D:5	CV5W,CV1W	-30mm	LB25	DMI1290B25R	DMI1290B25L	-	No side airbag, as curtain airbag is installed. For vehicles after minor change ('19 .11 ~), the error warning light of the airbag will light up unless the blue coupler itself under the genuine seat is relocated.
DELICA MINI	B34A,B35A,B37A,B38A	-20mm	B6	DMI1641B06R	DMI1641B06L	NPC001	Common to 2WD,4WD and EK SPACE(B3#W). Relocation of passenger seat pressure sensor is required. Use genuine base.
DELICA MINI	B34A,B35A,B37A,B38A	-20mm	LB9	DMI1641B09R	DMI1641B09L	NPC001	Common to 2WD,4WD and EK SPACE(B3#W). Relocation of passenger seat pressure sensor is required. Use genuine base.
DELICA SPACE GEAR	PF,PE,PD,PC,PB	-15mm	B4	DMI1220B04R	DMI1220B04L	-	
DIAMANTE	F11~F27	-10mm	B4	DMI1260B04R	DMI1260B04L	-	
DIAMANTE	F30,F40	-10mm	B4	DMI1270B04R	DMI1270B04L	-	
DINGO,DION	CQ,CR	-20mm	B4	DMI1280B04R	DMI1280B04L	-	
ECLIPSE	D32A	-10mm	B1	DMI1130B01R	DMI1130B01L	-	Spider (D53A) cannot be installed.
ECLIPSE	D27A	-20mm	B1	DMI1140B01R	DMI1140B01L	-	Offset toward door side is 10 mm. 2WD / D22A is unconfirmed. USA/GSR-4. Only for bottom filling sheet. Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
ECLIPSE CROSS	GK1W	-20mm	B36	DMI1150B36R	DMI1150B36L	NPC001	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
ECLIPSE CROSS	GK1W	-20mm	LB25	DMI1150B25R	DMI1150B25L	NPC001	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
ECLIPSE CROSS PHEV	GL3W	-20mm	B36	DMI1650B36R	DMI1650B36L	NPC002	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
ECLIPSE CROSS PHEV	GL3W	-20mm	LB25	DMI1650B25R	DMI1650B25L	NPC002	Passenger seat is equipped with a surface pressure sensor for the seat belt warning lamp.
EK SPACE	B11A	-20mm	B36	DMI1030B36R	DMI1030B36L	NPC001	Common to DAYZ ROOX(B21A).

EK SPACE EK X-SPACE	B34A,B35A,B37A,B38A	-20mm	B6	DMI1640B06R	DMI1640B06L	NPC001	Common to 2WD,4WD and ROOX(B4#W). Relocation of passenger seat pressure sensor is required. Use genuine base.
EK SPACE EK X-SPACE	B34A,B35A,B37A,B38A	-20mm	LB9	DMI1640B09R	DMI1640B09L	NPC001	Common to 2WD,4WD and ROOX(B4#W). Relocation of passenger seat pressure sensor is required. Use genuine base.
EK WAGON	H81W,H82W	-20mm	B4	DMI1010B04R	DMI1010B04L	-	Common to OTTI(H91W,H92W).
EK WAGON	B11W	-20mm	B6	DMI1020B06R	DMI1020B06L	-	Common to 2WD,4WD and DAYZ(B21W).
EK WAGON EK X	B33W,B36W B34W,B35W,B37W,B38W	-20mm	B36	DMI1630B36R	DMI1630B36L	NPC001	There is interference with the reclining dial width of 510 mm or more. Common to 2WD,4WD and DAYZ(B4#W). Relocation of passenger seat pressure sensor is required.
EK WAGON EK X	B33W,B36W B34W,B35W,B37W,B38W	-20mm	LB25	DMI1630B25R	DMI1630B25L	NPC001	Offset toward door side is 7 mm. There is interference with the reclining dial width of 510 mm or more. Common to 2WD,4WD and DAYZ(B4#W). Relocation of passenger seat pressure sensor is required.
EK X EV	B5AW	-20mm	B36	DMI1631B36R	DMI1631B36L	NPC001	There is interference with the reclining dial width of 510 mm or more. Common to 2WD,4WD and SAKURA(B6AW). Relocation of passenger seat pressure sensor is required.
EK X EV	B5AW	-20mm	LB25	DMI1631B25R	DMI1631B25L	NPC001	Offset toward door side is 7 mm. There is interference with the reclining dial width of 510 mm or more. Common to 2WD,4WD and SAKURA(B6AW). Relocation of passenger seat pressure sensor is required.
FTO	DE2A,DE3A	-10mm	B1	DMI1040B01R	DMI1040B01L	-	
GALANT FORTIS	CY4A	-20mm	B6	DMI1511B06R	DMI1511B06L	NPC001	Offset toward door side is 7 mm. Interferes with shoulder width exceeding 610 mm. Common to LANCER EVO10(CZ4A)
GALANT FORTIS SPORT BACK	CX4A	-20mm	B6	DMI1512B06R	DMI1512B06L	NPC001	Offset toward door side is 7 mm. Interferes with shoulder width exceeding 610 mm. Common to LANCER EVO10(CZ4A)
GALANT,LEGNUM	EA,EC	-20mm	B1	DMI1160B01R	DMI1160B01L	NPC001	
GRANDIS	NA4W	-20mm	B4	DMI1170B04R	DMI1170B04L	NPC001	
GTO	Z15A,Z16A	-10mm	B1	DMI1050B01R	DMI1050B01L	-	
i,i-MiEV	HA1W,HA3W,HA4W,HD4W	-10mm	B4	DMI1060B04R	DMI1060B04L	-	Seats with a convex bottom (such as AM19) are not compatible. Offset toward door side is 8 mm. Interferes with shoulder width exceeding 545 mm. Interferes with Side support width exceeding 459 mm. Some seats require door dial removal.

JEEP	J53~59	-10mm	B1	DMI1600B01R	DMI1600B01L	-	AM19 requires a 20mm spacer with or without electric function. Lifting up behind the seat is not possible. Floor drilling required. * * Right seat is on the rear console side, Left seat is on the rear left and right.
LANCER EVO7,8,9 LANCER SEDIA LANCER SEDIA WAGON	CT9A,CT9W,CS2A,CA5A	-20mm	B1	DMI1490B01R	DMI1490B01L	-	
LANCER EVO7,8,MR	CT9A	-20mm	B1	DMI1500B01R	DMI1500B01L	-	Lowdown rail for genuine RECARO seats. Use genuine slide rails.
LANCER EVO10	CZ4A	-20mm	B6	DMI1510B06R	DMI1510B06L	NPC001	Offset toward door side is 7 mm. Interferes with shoulder width exceeding 610 mm. Common to Galant Fortis(CY4A)、Sports back(CX4A).
MINICAB,MINICAB-MiEV	U61,62V,U67,U68	±0mm	B1	DMI1420B01R	-	-	Offset toward door side is 15 mm. Common to MINICAB(U61,U62),CLIPPER(U71V). When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat. Seats with a convex bottom (such as AM19) are not compatible. Seat rail conversion adapter cannot be installed.
MINICA	H20	-30mm	B4	DMI1330B04R	DMI1330B04L	-	Offset toward door side is 10 mm.
MINICA	H30,H31,H32	-30mm	B4	DMI1440B04R	DMI1440B04L	-	
MINICA	H42A,H42V,H47A,H47V	±0mm	B4	DMI1341B04R	DMI1341B04L	-	Common to TOPPO BJ(H42A,H47A).
MIRAGE	CM,CK,CJ,CD,CB	-10mm	B1	DMI1461B01R	DMI1461B01L	-	
MIRAGE	A05A	-25mm	B6	DMI1450B06R	DMI1450B06L	NPC001	
OUTLANDER	CW5W,GF7W,GF8W	-30mm	B36	DMI1090B36R	DMI1090B36L	NPC001	Common to RVR(GA3 '10.2~ GA4 '11.10~).
OUTLANDER	CW5W,GF7W,GF8W	-30mm	LB25	DMI1090B25R	DMI1090B25L	NPC001	Common to RVR(GA3 '10.2~ GA4 '11.10~).
OUTLANDER PHEV	GG2W,GG3W	-20mm	B36	DMI1110B36R	DMI1110B36L	NPC001	
OUTLANDER PHEV	GG2W,GG3W	-20mm	LB9	DMI1110B09R	DMI1110B09L	NPC001	
OUTLANDER PHEV	GN0W	-10mm	B36	DMI1700B36R	DMI1700B36L	NPC002	Passenger seat surface pressure sensor is for belt warning.
PAJERO	L040,L140	-20mm	B1	DMI1370B01R	DMI1370B01L	-	The seat belt anchor is fixed to the floor.
PAJERO	V10~40,V55	-25mm	B36	DMI1350B36R	DMI1350B36L	-	Offset toward console side is 5 mm.
PAJERO	V60,V70	-20mm	B4	DMI1360B04R	DMI1360B04L	NPC001	
PAJERO	V80,V90	-20mm	B36	DMI1380B36R	DMI1380B36L	NPC001	
PAJERO IO	H60,H70	-15mm	B4	DMI1390B04R	DMI1390B04L	-	
PAJERO Jr.	H57A	-20mm	B4	DMI1410B04R	DMI1410B04L	-	
PAJERO MINI	H56A	-20mm	B4	DMI1411B04R	DMI1411B04L	-	
PAJERO MINI	H53A,H58A	-15mm	B4	DMI1400B04R	DMI1400B04L	-	
ROSA	BE664	No data	B1	DMI1530B01R	DMI1530B01L	-	Mounting dimensions required. Micro bus (Handle center shifts by 30 mm or more) Front passenger's seat AM19 requires a 20mm spacer with or without electric function.
RVR	N13W,N23W	-15mm	B4	DMI1070B04R	DMI1070B04L	-	

RVR	N60W~N74W	-20mm	B16	DMI1080B16R	DMI1080B16L	-	
RVR	GA3,GA4	-30mm	B36	DMI1091B36R	DMI1091B36L	NPC001	Seat drop is from Model OUTLANDER(CW5W) specifications.
RVR	GA3,GA4	-30mm	LB25	DMI1091B25R	DMI1091B25L	NPC001	Seat drop is from Model OUTLANDER(CW5W) specifications.
TOPPO	H82A	-20mm	B4	DMI1011B04R	DMI1011B04L	-	
TOPPO BJ	H42A,H47A	-30mm	B4	DMI1340B04R	DMI1340B04L	-	Common to MINICA(H42A,H42V,H47A,H47V).
TOWN BOX	U61,U62	±0mm	B1	DMI1421B01R	-	-	<p>Offset toward door side is 15 mm.</p> <p>Common to MINICAB(U61,U62),CLIPPER(U71V).</p> <p>When installing the IS24 Recaro seat, the belt stays and bolts and nuts will interfere with the seat.</p> <p>Seats with a convex bottom (such as AM19) are not compatible.</p> <p>Seat rail conversion adapter cannot be installed.</p>