

— explanatory note —

The seat drop value described in the compatibility table is primarily a value relative to the original-equipment seat. It is measured by mounting a Recaro or Bride full bucket seat at the lowest position possible without the seat bottom interfering with the seat rail or vehicle floor. Differences may arise due to the position of the seat to be mounted (the position of the bolt holes), the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: If the original-equipment seat incorporates a height adjustment function, this value is relative to the lowest position.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

NISSAN

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
AVENIR	W10	-10mm	S1	DNN1100S01R	DNN1100S01L	-	2WD
AVENIR,EXPERT	W11	-10mm	S1	DNN1110S01R	DNN1110S01L	NPC001	2WD
AVENIR,EXPERT	NW11	-10mm	S1	DNN1120S01R	DNN1120S01L	NPC001	4WD
AD VAN	Y10	-10mm	S1	DNN1131S01R	DNN1131S01L	-	2WD
AD VAN	NY10	-10mm	S1	DNN1141S01R	DNN1141S01L	-	4WD
AD VAN	Y11,NY11	-10mm	S4	DNN1151S04R	DNN1151S04L	-	
AD VAN,AD EXPERT	Y12,NY12	-10mm	S16	DNN1161S16R	DNN1161S16L	-	Offset toward door side is 7 mm. It is common to 2WD and 4WD.
ATLAS	TZ2F24	No data	S4	DNN2460S04R	-	-	Mounting dimensions required.
BASSARA	NU30,U30	-20mm	S4	DNN2142S04R	DNN2142S04L	NPC001	
BLUEBIRD	U14	-10mm	S1	DNN1910S01R	DNN1910S01L	-	2WD
BLUEBIRD	NU14	-10mm	S1	DNN1920S01R	DNN1920S01L	NPC001	4WD
BLUEBIRD SYLPHY	G10	-25mm	S1	DNN1930S01R	DNN1930S01L	NPC001	It cannot be installed on 4WD / NG10.
BLUEBIRD SYLPHY	G11,NG11	-15mm	S16	DNN1940S16R	DNN1940S16L	-	Offset toward door side is 15 mm.
CARAVAN	E25	±0mm	S1	DNN1230S01R	DNN1230S01L	-	
NV350 CARAVAN	E26	+15mm	S1	DNN1070S01R	-	-	
CEDRIC,GLORIA	Y33	-10mm	S4	DNN1521S04R	DNN1521S04L	NPC001	
CEDRIC,GLORIA	Y34	-20mm	S4	DNN1530S04R	DNN1530S04L	NPC001	2WD
CEFIRO	A31	-10mm	S1	DNN1540S01R	DNN1540S01L	-	
CEFIRO,CEFIRO WAGON	A32	-20mm	S4	DNN1550S04R	DNN1550S04L	NPC001	
CEFIRO	A33	-20mm	S4	DNN1560S04R	DNN1560S04L	NPC001	
CHERRY	E10	-30mm	S1	DNN2350S01R	DNN2350S01L	-	The seat belt anchor is fixed to the floor.
CIMA	Y33	-10mm	S4	DNN1520S04R	DNN1520S04L	NPC001	
CIMA	GNF50	±0mm	S4	DNN1330S04R	DNN1330S04L	NPC001	4WD
CIMA	GF50,HF50	±0mm	S4	DNN1340S04R	-	NPC001	2WD
CIVILIAN	W40,41	+20mm	S1	DNN1370S01R	-	-	1988.5~1999.1 1-position offset seat rail.
CIVILIAN	W40,41	+30mm	S1	-	DNN1360S01L	-	1988.5~1999.1 Fixed on left side wall (front and rear pitch about 305 mm). Offset toward console is 30 mm.
CIVILIAN	W40,41	+30mm	S1	-	DNN1350S01L	-	Fixed to engine cover Details such as year are unknown.
CLIPPER	U71V,U72V	±0mm	S1	DNN2140S01R	-	-	Offset toward door side is 15 mm. Common to TOWN BOX(U61W,U62W),MINICAB(U61V,U62V). Seat rail conversion adapter cannot be installed. 1-position offset seat rail.

CUBE	Z10	-20mm	S4	DNN1240S04R	DNN1240S04L	-	2WD
CUBE	Z11	-15mm	S36	DNN1250S36R	DNN1250S36L	NPC001	2WD
CUBE	Z12,NZ12	-20mm	S16	DNN1260S16R	DNN1260S16L	-	It is common to 2WD and 4WD.
DATSUN TRUCK	D20,D21	-20mm	S4	DNN1691S04R	DNN1691S04L	-	
DATSUN TRUCK	D22	-15mm	S1	DNN1590S01R	DNN1590S01L	-	
DATSUN TRUCK(SQUARE H	720	-20mm	S4	DNN1600S04R	DNN1600S04L	-	The seat belt anchor is fixed to the floor.
DAYZ	B21W	-20mm	S6	DNN1650S06R	DNN1650S06L	-	It is common to 2WD and 4WD.
DAYZ	B43W,B44W, B45W B46W,B47W,B48W	-20mm	S36	DNN2310S36R	DNN2310S36L	NPC001	Common to 2WD,4WD and EK WAGON(B3#W). Relocation of passenger seat pressure sensor is required.
DAYZ ROOX	B21A	-20mm	S36	DNN1660S36R	DNN1660S36L	NPC001	
DUALIS	J10,NJ10	-20mm	S16	DNN1670S16R	DNN1670S16L	NPC001	It is common to 2WD and 4WD. Offset toward door side is 8 mm.
ELGRAND	E50	-10mm	S16	DNN1190S16R	DNN1190S16L	-	
ELGRAND	E51,NE51	-20mm	S16	DNN1200S16R	DNN1200S16L	-	~'04/8 Before M/C. It is common to 2WD and 4WD.
ELGRAND	E51,NE51	-20mm	S16	DNN1210S16R	DNN1210S16L	-	'04/9~ After M/C. It is common to 2WD and 4WD.
ELGRAND	E52	-30mm	S36	DNN1220S36R	DNN1220S36L	NPC001	Offset toward door side is 5 mm.
FAIRLADY	SR311	No data	S1	DNN1790S01R	DNN1790S01L	-	
FAIRLADY Z	S30	No data	S1	DNN1810S01R	DNN1810S01L	-	Vertically fixed to the floor both front and rear, and fixed with nuts from inside the fixing part.
FAIRLADY Z	S30,GS30	+10mm	S4	DNN1800S04R	DNN1800S04L	-	Fix it at an angle to the floor both front and rear and bolt it to the floor.
FAIRLADY Z	Z31	-20mm	S1	DNN1820S01R	DNN1820S01L	-	
FAIRLADY Z	Z32	±0mm	S4	DNN1830S04R	DNN1830S04L	-	
FAIRLADY Z	Z33	-20mm	S1	DNN1840S01R	DNN1840S01L	NPC001	Offset toward door side is 13 mm. Vehicles with active seats require a canceller (NPC001×1 pcs).
FAIRLADY Z	Z34,RZ34	±0mm	S4	DNN1850S04R	DNN1850S04L	NPC001	Three-step adjustment For seats with a convex bottom, watch for interference at the rearmost part of the seat bottom. Offset toward door side is 5 mm. Interferes with shoulder width exceeding 570 mm.
FAIRLADY Z	Z34,RZ34	-25mm	S1	DNN2290S01R	DNN2290S01L	NPC001	Superlow model. Offset toward door side is 15 mm. Interferes with shoulder width exceeding 560 mm.
FAIRLADY Z	Z34,RZ34	-50mm	SSD	DNN1860SSDR	-	NPC001	Interferes with shoulder width exceeding 580 mm.
FUGA	Y50	-10mm	S4	DNN1770S04R	DNN1770S04L	NPC001	It is necessary to move the position memory. 4WD / NY50 is unconfirmed.
FUGA	KNY51	-10mm	S6	DNN1780S06R	DNN1780S06L	NPC001	4WD Offset toward door side is 7 mm. 2WD,hybrid/Y,KY51 is unconfirmed.
GTR	R35	+15mm	S1	DNN1040S01R	DNN1040S01L	NPC001	Offset toward door side is 15 mm. Interferes with shoulder width exceeding 580 mm.
GTR	R35	-10mm	S1	-	DNN1010S01L	NPC001	For left seat. Superlow model.

GTR	R35	-10mm	S1	DNN1020S01R	-	NPC001	For right seat. Superlow model. Interferes with shoulder width exceeding 580 mm. Offset toward door side is 20 mm. 1-position offset seat rail.
GTR	R35	-50mm	SSD	DNN1030SSDR	DNN1030SSDL	NPC001	Interferes with shoulder width exceeding 580 mm. Offset toward door side is 20 mm.
KIKS	H59A	-15mm	S4	DNN2360S04R	DNN2360S04L	-	Common to PAJERO MINI(H53,H58).
KIKS	P15	-20mm	S6	DNN2300S06R	DNN2300S06L	NPC002	Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required.
KIKS	P15	-20mm	LS9	DNN2300S09R	DNN2300S09L	NPC002	Relocation of passenger seat pressure sensor is required.
JUKE	F15,YF15	±0mm	S36	DNN2330S36R	DNN2330S36L	NPC001	Offset toward door side is 5 mm. 4WD / NF15 is unconfirmed.
LAFESTA	B30,NB30	-20mm	S4	DNN2060S04R	DNN2060S04L	NPC001	
LAFESTA	CWEFWN,CWEAWN	-20mm	S36	DNN2390S36R	DNN2390S36L	NPC001	Offset toward door side is 5 mm. Cannot be attached to passenger seat cup holder (table).
LAUREL	C32	-30mm	S4	DNN1411S04R	-	-	
			S1	-	DNN1411S01L	-	
LAUREL	C33	-10mm	S1	DNN2120S01R	DNN2120S01L	-	2WD
LAUREL	C34	-10mm	S1	DNN2110S01R	DNN2110S01L	-	2WD
LAUREL	C35	-10mm	S4	DNN2100S04R	DNN2100S04L	NPC001	2WD
LAUREL	C35	-25mm	S1	DNN2340S01R	DNN2340S01L	NPC001	2WD Superlow model.
LEAF	ZE0	-10mm	S6	DNN2070S06R	DNN2070S06L	NPC001	
LEAF	ZE1	-10mm	S6	DNN2160S06R	DNN2160S06L	NPC002	
LIBERTY	NM12,M12	-20mm	S4	DNN2080S04R	DNN2080S04L	NPC001	
LEOPARD	F31	-30mm	S4	DNN1412S04R	-	-	
			S1	-	DNN1412S01L	-	
LEOPARD	Y33	-10mm	S4	DNN1522S04R	DNN1522S04L	NPC001	
MARCH	K11	-10mm	S4	DNN1970S04R	DNN1970S04L	-	2WD
MARCH	K11	-90mm	S1	DNN2550S01R	DNN2550S01L	-	2WD Superlow model. Interferes with shoulder width exceeding 560 mm. Offset toward door side is 20 mm.
MARCH	NK11	-10mm	S6	DNN1980S06R	DNN1980S06L	-	4WD Offset toward door side is 13 mm.
MARCH	K12	-30mm	S4	DNN1990S04R	DNN1990S04L	NPC001	Offset toward door side is 10 mm.
MARCH	K13	-20mm	S36	DNN2000S36R	DNN2000S36L	NPC001	It is common to 2WD and 4WD. Offset toward door side is 10 mm.
MARCH	K13	-20mm	LS9	DNN2000S09R	DNN2000S09L	NPC001	It is common to 2WD and 4WD. Offset toward door side is 10 mm.
MARCH	K13	-90mm	S1	DNN2280S01R	DNN2280S01L	NPC001	Superlow model. It is common to 2WD and 4WD. Offset toward door side is 10 mm.
MOCO	MG21S	-15mm	S4	DNN2030S04R	DNN2030S04L	-	Common to WAGON-R(MC11S,MC22S),MR-WAGON(MF21S),
MOCO	MG22S	-20mm	S16	DNN2450S16R	DNN2450S16L	-	Common to WAGON-R(MH21S,MH22S),MR-WAGON(MF22S),

MOCO	MG33S	-20mm	S36	DNN2040S36R	DNN2040S36L	NPC001	Common to WAGON-R(MH34S,MH44S),MR-WAGON(MF33S), SPACIA(MK32S,MK42S), FLAIR(MJ34S,MJ44S).
MURANO	Z50,NZ50	-35mm	S16	DNN2010S16R	DNN2010S16L	-	
MURANO	NZ51	-10mm	S16	DNN2020S16R	DNN2020S16L	NPC001	Requires original-equipment tool for 16-mm hexagon floor bolts.
NAVARA	D23型	-20mm	S1	DNN1050S01R	DNN1050S01L	NPC002	Double pickup. Offset toward door side is 10 mm. Relocation of passenger seat pressure sensor is required.
NOTE	E11,NE11	-25mm	S16	DNN1700S16R	DNN1700S16L	-	It is common to 2WD and 4WD. Offset toward door side is 15 mm.
NOTE	E12,NE12	-20mm	S6	DNN1710S06R	DNN1710S06L	-	It is common to 2WD and 4WD. Offset toward door side is 15 mm.
NOTE	E12,NE12	-20mm	LS9	DNN1710S09R	DNN1710S09L	-	It is common to 2WD and 4WD. Offset toward door side is 7 mm.
NOTE e-POWER	HE12,SNE12	-10mm	S36	DNN1720S36R	DNN1720S36L	-	Offset toward door side is 12 mm. For seats with a convex bottom, watch for interference at the rearmost part of the seat bottom. A seat with a projecting bottom will interfere with the battery and outlet located on the floor. (Can be installed if the seat is raised.)
NOTE,NOTE AURA	E13,SNE13,FE13,FSNE13	±0mm	S36	DNN2470S36R	DNN2470S36L	NPC001	It is common to 2WD and 4WD. Offset toward door side is 10 mm.
NOTE,NOTE AURA	E13,SNE13,FE13,FSNE13	-30mm	S6	DNN2480S06R	DNN2480S06L	NPC001	Superlow model. It is common to 2WD and 4WD. Offset toward door side is 10 mm. It interferes with the rear air conditioner duct of 4WD vehicles and cold region specification vehicles.
NOTE,NOTE AURA	E13,SNE13,FE13,FSNE13	-10mm	LS9	DNN2490S09R	DNN2490S09L	NPC001	It is common to 2WD and 4WD.
NV200 VANETTE	M20,VM20	±0mm	S1	DNN1060S01R	DNN1060S01L	-	
NV350 CARAVAN	E26	+15mm	S1	DNN1070S01R	-	-	Passenger seat is unconfirmed.
NV400	-	-10mm	S36	DNN1080S36R	-	-	
OTTI	H91W,H92W	-20mm	S4	DNN2130S04R	DNN2130S04L	-	Common to eK-WAGON(H81W,H82W)
PRAIRIE JOY	M11	-15mm	S4	DNN1950S04R	DNN1950S04L	-	
PRESAGE	NU30,U30	-20mm	S4	DNN2141S04R	DNN2141S04L	NPC001	
PRESAGE	U31,NU31	-20mm	S16	DNN1960S16R	DNN1960S16L	NPC001	Excludes cold weather vehicles
PRESAGE	U31,NU31	-20mm	S4	DNN1960S04R	DNN1960S04L	NPC001	Cold region specification vehicle
PRIMERA	P10	-10mm	S4	DNN1870S04R	DNN1870S04L	-	
PRIMERA	P11	-10mm	S1	DNN1880S01R	DNN1880S01L	NPC001	2WD
PRIMERA	NP11	-10mm	S1	DNN1900S01R	DNN1900S01L	NPC001	4WD
PRIMERA	P12	-20mm	S1	DNN1890S01R	DNN1890S01L	NPC001	2WD Offset toward door side is 5 mm.
PULSAR	N14	-10mm	S1	DNN1740S01R	DNN1740S01L	-	2WD
PULSAR	NN14	-20mm	S1	DNN1750S01R	DNN1750S01L	-	4WD
PULSAR	N15	±0mm	S1	DNN1760S01R	DNN1760S01L	-	4WD / NN15 cannot be installed.
RASHEEN	NB14	-20mm	S1	DNN2050S01R	DNN2050S01L	-	4WD
RNESSA	NN30,N30	-20mm	S4	DNN2140S04R	DNN2140S04L	NPC001	
ROOX	B44A,B45A,B47A,B48A	-20mm	S6	DNN2320S06R	DNN2320S06L	NPC001	Common to 2WD,4WD and EK SPACE(B3#A).
ROOX	B44A,B45A,B47A,B48A	-20mm	LS9	DNN2320S09R	DNN2320S09L	NPC001	Common to 2WD,4WD and EK SPACE(B3#A). Relocation of passenger seat pressure sensor is required. Use genuine base.
SAFARI	Y60	-20mm	S4	DNN1320S04R	DNN1320S04L	-	PATROL 1987.9~1997.9
SAFARI	Y61	-20mm	S4	DNN1310S04R	DNN1310S04L	-	
SAKURA	B6AW	-20mm	S36	DNN2311S36R	DNN2311S36L	NPC001	It is common to 2WD and 4WD.

SERENA	NC24,C24	-30mm	S16	DNN1570S16R	DNN1570S16L	-	It is common to 2WD and 4WD.
SERENA	C25,C26	-25mm	S36	DNN1580S36R	DNN1580S36L	NPC001	It is common to 2WD and 4WD.
SERENA	C27	-25mm	S36	DNN1581S36R	DNN1581S36L	NPC002	It is common to 2WD and 4WD. e-POWER cannot be installed.
SERENA e-POWER	HC27,HFC27	-20mm	S36	DNN2440S36R	DNN2440S36L	NPC002	e-POWER only.
SERENA	C28,FC28	-25mm	S36	DNN1582S36R	DNN1582S36L	NPC002	It is common to 2WD and 4WD. e-POWER cannot be installed. Not confirmed for vehicles equipped with center console box.
SERENA e-POWER	GC28,GFC28	-20mm	S36	DNN2540S36R	DNN2540S36L	NPC002	e-POWER only. Interferes with shoulder width exceeding 560 mm. Not confirmed for vehicles equipped with center console box.
SYLPHY	TB17	±0mm	S36	DNN1380S36R	DNN1380S36L	NPC001	Offset toward door side is 5 mm.
SILVIA,180SX	S13,14	-20mm	S1	DNN2260S01R	-	-	Superlow model. 1-position offset seat rail.
SILVIA,180SX	S13,14	-10mm	S1	-	DNN1400S01L	-	
SILVIA,180SX	S13,14	-40mm	SSD	DNN1390SSDR	-	-	
SILVIA	S15	-20mm	S1	DNN2261S01R	-	NPC001	Superlow model. 1-position offset seat rail.
SILVIA	S15	-10mm	S1	-	DNN1401S01L	NPC001	
SILVIA	S15	-40mm	SSD	DNN1391SSDR	-	NPC001	
SKYLINE	GC10	No data	S1	DNN2150S01R	DNN2150S01L	-	Superlow model. Seat rail conversion adapter cannot be installed. 1-position offset seat rail.
SKYLINE	GC10	No data	S1	DNN2390S01R	DNN2390S01L	-	Compared to DNN2150, only the front is increased by 15mm.
SKYLINE	GC10	No data	S6	DNN2400S06R	DNN2400S06L	-	Compared to DNN2150, both front and rear are increased by 30mm.
SKYLINE	R31	-30mm	S4	DNN1410S04R	-	-	
SKYLINE			S1	-	DNN1410S01L		
SKYLINE	R32,33	-20mm	S1	DNN2271S01R	-	-	2WD Superlow model. 1-position offset seat rail.
SKYLINE	R32,33	-10mm	S1	-	DNN1431S01L	-	2WD
SKYLINE	R32,33	-40mm	SSD	DNN1421SSDR	-	-	Offset toward door side is 15 mm.
SKYLINE	NR32,33,34	-20mm	S1	DNN2270S01R	-	NPC001	4WD Superlow model. 1-position offset seat rail.
SKYLINE	NR32,33,34	-10mm	S1	-	DNN1430S01L	NPC001	4WD
SKYLINE	NR32,33,34	-40mm	SSD	DNN1420SSDR	-	-	4WD Offset toward door side is 15 mm.
SKYLINE	ER34,HR34	-20mm	S1	DNN1440S01R	DNN1440S01L	NPC001	2WD
SKYLINE	V35	-10mm	S4	DNN1450S04R	DNN1450S04L	NPC001	Vehicles with active seats require a canceller (NPC001×1 pcs).
SKYLINE COUPE	CPV35	-20mm	S1	DNN1460S01R	DNN1460S01L	NPC001	Vehicles with active seats require a canceller (NPC001×1 pcs).
SKYLINE	V36	-10mm	S4	DNN1470S04R	DNN1470S04L	NPC001	For 2WD vehicles. 4WD/NV36 is unconfirmed.
SKYLINE COUPE	CKV36	-10mm	S1	DNN1480S01R	DNN1480S01L	NPC001	Offset toward door side is 18 mm.
SKYLINE	V37	-25mm	S1	DNN2370S01R	DNN2380S01L	NPC001	For 2WD vehicles. 4WD/NV37 is unconfirmed. Hybrid vehicle is unconfirmed.
SKYLINE CROSSOVER	J50,NJ50	-20mm	S6	DNN1490S06R	DNN1490S06L	NPC001	It is common to 2WD and 4WD.

STAGEA	WC34	-10mm	S4	DNN1500S04R	DNN1500S04L	NPC001	It is common to 2WD and 4WD.
STAGEA	M35	-10mm	S4	DNN1510S04R	DNN1510S04L	NPC001	Vehicles with active seats require a canceller (NPC001×1 pcs).
SUNNY	B310	No data	S1	DNN1270S01R	DNN1270S01L	-	Excluding B311 1977.11~1981.9
SUNNY	B13	-10mm	S1	DNN1280S01R	DNN1280S01L	-	2WD
SUNNY	B14	±0mm	S1	DNN1290S01R	DNN1290S01L	-	2WD
SUNNY	B15	-10mm	S1	DNN1300S01R	DNN1300S01L	-	2WD
TEANA	J31	-20mm	S4	DNN1610S04R	DNN1610S04L	NPC001	4WD/NJ31 unconfirmed.
TEANA	J32	-20mm	S16	DNN1620S16R	DNN1620S16L	NPC001	2WD
TERRANO	R50	-15mm	S4	DNN1680S04R	DNN1680S04L	-	
TERRANO,DATSUN TRUCK	D21	-20mm	S4	DNN1690S04R	DNN1690S04L	-	
TIIDA, TIIDA LATIO	C11,NC11	-25mm	S16	DNN1630S16R	DNN1630S16L	-	It is common to 2WD and 4WD. Offset toward door side is 15 mm.
TINO	V10	-20mm	S4	DNN1640S04R	DNN1640S04L	NPC001	
UD 10t	-	-20mm	S6	DNN1090S06R	-	-	Mounting dimensions required.(There are 2 types.) Slide rail cannot be connected.
WINGROAD	Y10	-10mm	S1	DNN1130S01R	DNN1130S01L	-	2WD
WINGROAD	NY10	-10mm	S1	DNN1140S01R	DNN1140S01L	-	4WD
WINGROAD	Y11,NY11	-10mm	S4	DNN1150S04R	DNN1150S04L	-	It is common to 2WD and 4WD.
WINGROAD	Y12,NY12	-10mm	S16	DNN1160S16R	DNN1160S16L	-	Offset toward door side is 7 mm. It is common to 2WD and 4WD.
X-TRAIL	NT30,T30	-20mm	S4	DNN1170S04R	DNN1170S04L	-	It is common to 2WD and 4WD.
X-TRAIL	NT31,T31	-20mm	S16	DNN1671S16R	DNN1671S16L	NPC001	Offset toward door side is 8 mm.
X-TRAIL	NT32,T32	-30mm	S36	DNN1180S36R	DNN1180S36L	NPC001	It is common to 2WD and 4WD.
X-TRAIL	T33,SNT33	±0mm	S36	DNN2510S36R	DNN2510S36L	NPC001	It is common to 2WD and 4WD.
X-TRAIL	T33,SNT33	-10mm	LS9	DNN2520S09R	DNN2520S09L	NPC001	It is common to 2WD and 4WD.