

The seat drop value described in the compatibility table is primarily a value relative to the original-equipment seat.

It is measured by mounting a Recaro Reclining seat.

— **explanatory note** — Differences may arise due to the position of the thickness and shape of the bottom of the seat, and seat settling due to aging of the original-equipment seat.

Note: If the original-equipment seat incorporates a height adjustment function, this value is relative to the lowest position.

Note: As a general rule, driver's seat data (passenger seats have different values depending on the presence or absence of height adjustment function)

USA

CHEVROLET

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
ASTRO	CL14G,CM14G	-40mm	B1	ICT1030B01R	ICT1030B01L	-	'02 model Confirmation of fixed pitch is required. Front and back 243mm×left and right 356mm
ASTRO	CL14G,CM14G	-30mm	B4	ICT1040B04R	ICT1040B04L	-	'03 model Confirmation of fixed pitch is required. Front and back 318mm×left and right 324mm The seat belt anchor is fixed to the floor.
BLAZER	CT34G	-20mm	B4	ICT1010B04R	ICT1010B04L	-	
C1500	-	No data	B36	ICT1060B36R	ICT1060B36L	-	Confirmation of fixed pitch is required. Front and back 270mm×left and right 340mm
CAMARO	CF43,CF45	-10mm	B1	ICT1090B01R	ICT1090B01L	-	COUPE
CAMARO	CF43,CF45	±0mm	B1	ICT1130B01R	ICT1130B01L	-	Convertible
CAMARO	-	No data	B6	ICT1180B06R	ICT1180B06L	NPC002	'17/11~ Relocation of the slide sensor and pressure sensor is required.
CORVETTE C6	-	No data	B6	ICT1240B06R	ICT1240B06L	NPC003	Offset toward door side is 23 mm. Need to relocate the slide sensor and surface pressure sensor. Can only be equipped with BRIDE GIAS and STRADIA.
EXPRESS	-	No data	B36	ICT1230B36R	ICT1230B36L	-	Use genuine base. Confirmation of fixed pitch is required. Front and back 332mm×left and right 360mm.
OPTRA WAGON	NA35Z	-10mm	B4	ICT1050B04R	ICT1050B04L	NPC001	

CHRYSLER/CHRYSLER JEEP

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
300C	LX36	-10mm	B36	ICR1010B36R	ICR1010B36L	-	
CHEROKEE	7M	-20mm	B4	ICR1060B04R	ICR1060B04L	-	'88~'94/09 The seat belt anchor is fixed to the floor.
CHEROKEE	7M	-20mm	B4	ICR1070B04R	ICR1070B04L	-	'94/10~'97/04
CHEROKEE	7M	-20mm	B4	ICR1080B04R	ICR1080B04L	-	'97/05~'02

CHEROKEE	KJ37	-20mm	B4	ICR1050B04R	ICR1050B04L	-	
COMMANDER	XH47,XH57	No data	B16	ICR1021B16R	ICR1021B16L	-	Use genuine base.
COMPASS	M624	-20mm	B36	ICR1160B36R	ICR1160B36L	NPC002	Relocation of the slide sensor and pressure sensor is required.
GRAND CHEROKEE	WH47,WH57	No data	B16	ICR1020B16R	ICR1020B16L	-	Use genuine base.
PTCRUISER	PT2K20	-10mm	B4	ICR1030B04R	ICR1030B04L	NPC001	Common to cabriolet.
VOYAGER	GS33S	-20mm	B4	ICR1090B04R	ICR1090B04L	-	
WRANGLER	YJ S8MX,S8H,S8C	No data	B6	ICR1120B06R	ICR1120B06L	-	
WRANGLER	TJ40S	-20mm	B4	ICR1130B04R	ICR1130B04L	-	'96/10~'03 Seat belt anchor fixed vertically.
WRANGLER	TJ40S	-20mm	B4	ICR1140B04R	ICR1140B04L	-	'04~ Seat belt anchor fixed horizontally.
WRANGLER	JK38S	-20mm	B36	ICR1100B36R	ICR1100B36L	NPC001	2dr. Interferes with shoulder width exceeding 500 mm. Confirmation of fixed pitch is required. Door side front and rear 577mm
WRANGLER	JK38S	-20mm	LB9	ICR1100B09R	ICR1100B09L	NPC001	2dr. Interferes with shoulder width exceeding 500 mm. Confirmation of fixed pitch is required. Door side front and rear 577mm
WRANGLER	JK38S	±0mm	B36	ICR1150B36R	ICR1150B36L	NPC001	2dr. Interferes with shoulder width exceeding 500 mm. Confirmation of fixed pitch is required. Door side front and rear 445mm
WRANGLER	JK38S	±0mm	LB9	ICR1150B09R	ICR1150B09L	NPC001	2dr. Interferes with shoulder width exceeding 500 mm. Confirmation of fixed pitch is required. Door side front and rear 445mm
WRANGLER	JK36S	±0mm	B36	ICR1151B36R	ICR1151B36L	NPC001	2dr. Interferes with shoulder width exceeding 500 mm. Confirmation of fixed pitch is required. Door side front and rear 445mm
WRANGLER	JK36S	±0mm	LB9	ICR1151B09R	ICR1151B09L	NPC001	2dr. Interferes with shoulder width exceeding 500 mm. Confirmation of fixed pitch is required. Door side front and rear 445mm
WRANGLER	JK36L,JK38L	-25mm	B36	ICR1101B36R	ICR1101B36L	NPC001	4dr. Interferes with shoulder width exceeding 540 mm.
WRANGLER	JK36L,JK38L	-25mm	LB9	ICR1101B09R	ICR1101B09L	NPC001	4dr. Interferes with shoulder width exceeding 540 mm.
WRANGLER	JL20L,JL36L,JL36S	-20mm	B6	ICR1170B06R	ICR1170B06L	NPC002	4dr. Relocation of the driver's seat weight sensor and passenger seating switch is required. Common to JL36S (2dr).

DODGE

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
------------	------------	-----------	------	----------------	---------------	----------	---------

CHARENGER	-	No data	B6	IDE1020B06R	IDE1020B06L	NPC001	'08 model Confirmation of fixed pitch is required. Front and back 393mm×left and right 422mm Offset toward door side is 8 mm. Relocation of the slide sensor and pressure sensor is required.
RAM	-	No data	B6	IDE1010B06R	IDE1010B06L	-	Use genuine base. Confirmation of fixed pitch is required. Front and back 245mm×left and right 376mm

Ford

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
ECO SPORT	MAJUEJ	-10mm	B36	IFD1010B36R	IFD1010B36L	No data	
EXION	UA-CP8W	-15mm	B4	IFD1100B04R	IFD1100B04L	NPC001	2WD
EXION	TA-CP8W	-15mm	B4	IFD1110B04R	IFD1110B04L	NPC001	4WD
ESCAPE	EPEWF	-10mm	B4	IFD1120B04R	IFD1120B04L	NPC001	
EXPLORER	1FMXU	-10mm	B4	IFD1040B04R	IFD1040B04L	NPC004	Offset toward door side is 20 mm.
EXPLORER	1FMEU74,1FMWU74	-20mm	B4	IFD1050B04R	IFD1050B04L	-	'01/10~'05/10 The pretensioner is secured with a rivet.
EXPLORER	1FMEU74,1FMWU74	-20mm	B4	IFD1060B04R	IFD1060B04L	NPC001	'05/11~'11/04 Offset toward door side is 15 mm. Relocation of the slide sensor is required.
MUSTANG	-	-30mm	B6	IFD1070B06R	IFD1070B06L	NPC001	'06~'13 Relocation of the slide sensor is required.

HUMMER

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
HUMMER H3	-	-10mm	B4	IHR1030B04R	IHR1030B04L	-	H2 cannot be installed. All seats equipped with pressure sensors.

TESLA

Model Name	Model Code	Seat Drop	Type	Right Part No.	Left Part No.	Side SRS	Remarks
Model 3	3L13,3L23,3L23P	-15mm	B1	ITA1000B01R	ITA1000B01L	NPC002	Driving seat(NPC002×2 pcs) Since the surface pressure sensor is special, it is necessary to relocate the OEM part or use a dedicated harness from an third party. (specialty garage recommended for installation).
Model Y	YL3YT,YL3YPT	-5mm	B1	ITA1010B01R	ITA1010B01L	NPC002	Driving seat(NPC002×2 pcs) Since the surface pressure sensor is special, it is necessary to relocate the OEM part or use a dedicated harness from an third party. (specialty garage recommended for installation).